

SEPARATE SLURRY IN A HURRY

CENTRIFUGES FOR INDUSTRIAL PROCESSING



 **ALLIED**
Centrifuge Technologies

iX SERIES

 **ALLIED**
Industrial Dynamics
www.alliedindyn.com

- Rendering
- Surimi
- Bio fuels
- Technical Fats
- Edible fats & oils (FX range)
- Mechanically de-boned meat
- Poultry by-products
- Blood Plasma
- Blood meal
- Gelatin
- Beef & pork by-products
- slaughterhouse wastewater
- DAF Skimmings
- Slop oil
- Tank cleaning

Unit	Feed Capacity	Phase	Empty Decanter Weight	Beach Angle	Total Installed Power	Bowl Diameter
iX100	0.5-2 M3/h (3-44 gpm)	2 or 3	318 kg (700 bs)	20° 15° 10° 8°	7hp	152 mm (6")
iX200	1-10 M3/h (3-44 gpm)	2 or 3	900 kg (1984 lbs)	20° 15° 10° 8°	15hp	254 mm (10")
iX300	5-14 M3/h (20-60 gpm)	2 or 3	1752 kg (3800 lbs)	20° 15° 10° 8°	40hp	356 mm (14")
iX400	17-30 M3/h (75-125 gpm)	2 or 3	4200 kg (9259 lbs)	20° 15° 10° 8°	65hp	457 mm (18")
iX500	35-55 M3/h (154-242 gpm)	2 or 3	6500 kg (14330 lbs)	20° 15° 10° 8°	120hp	559 mm (22")
iX600	45-90 M3/h (200-400 gpm)	2 or 3	9700 kg (21385 lbs)	20° 15° 10° 8°	150hp	660 mm (26")
iX700	68-159 M3/h (300-700 gpm)	2 or 3	15800 kg (34833 lbs)	20° 15° 10° 8°	200hp	762 mm (30")